

Stay safe.

RESiSecurity

Security Camera



Features

- H.265/H.264 5MP IP/Network Dual Light Full Color
- Up to 5 megapixel high resolution
- Max. 2592*1944@25fps (50Hz/60Hz)
- Support RTSP&Onvif (17.2 with profile S)
- Compatible with many third-party NVRs and CMS
- Support multiply Web Browsers: IE/Firefox/Chrome/Safari
- Day/Night, AWB/MWB,BLC, 3D-DNR,Shutter, IR-CUT
- D-WDR,Mirror, Image Flip etc.
- 2.8mm F1.6 fixed lens

▶▶ Camera Specifications

Image Sensor:	1/3" High sensitivity CMOS
Signal System:	PAL/NTSC
Min. Illumination:	Color: 0.05lux @(F1.6, AGC ON), 0 lux with IR or light
Shutter Time:	1/25 s to 1/10,000 s
Lens:	2.8mm F1.6 fixed lens
Day&Night:	2pcs Homologous Dual Light (Warm Light+IR LED Light)
Image Enhancement:	BLC/3D DNR
Motion Detection:	Support
Privacy Protection:	Support(4 Self-customized Areas)
Smart function:	Humanoid detection
Illumination for Infrared Switching:	0.5~3Lux
Infrared Wavelength:	850nm
Mimumum Illumination:	0 Lux(IR ON)
LED Light Distance	IR 25m/Warm light 20m

Model
Resi-504color5MP



Night Vision Camera

5MP security camera with full-color night vision, high resolution (2592x1944), H.265 compression for efficient storage.



RESiSecurity

resisecurity.com

©2024- All rights reserved.
Product specifications and availability
subject to change without notice.

Stay safe.

RESiSecurity

Security Camera

Model
Resi-504color5MP

▶▶ Network

Network Protocols:	"Http/Https, TCP/IP, IPv4/v6, UPNP, RTSP/RTMP,FTP, UDP, SMTP, NTP, DHCP, DNS, DDNS,IP Search (Support P2P, NVR, NVS etc.)"
General Function:	Anti-Flicker, heartbeat, password protection, privacy mask, Watermark
System Compatibility:	ONVIF(17.2 with profile S)
On-line Viewing	Max. Support 2 Users Simultaneously

▶▶ Interface

Communication Interface:	1 RJ45 10M / 100M Ethernet Interface
Audio Interface:	RCA Audio input/output Interface (Optional)
Alarm in/out interface	Support (1ch) (Optional)
SD card interface	No
DC Power Plug:	DC Power Femate Interface/POE(optional)

▶▶ Image

Image Resolution:	Main stream:2592*1944(5MP)/2560x1440(4MP)/1920x1080(1080p) sub stream:720x480(D1)/640x480(VGA)/640x360/352x288(CIF)
Frame Rate:	Main stream:25fps(5MP) max. sub stream:25fps max.
Stream:	two streams
Image Settings:	3D NR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App.
Day/Night mode	Support Full color mode auto switch mode (BW with IR led). Trigger mode(Humanoid triggers white light at night).

▶▶ Audio

Audio Compression:	G711U/G711A/AAC
Audio Bitrate	64K(G711)/16k(AAC)
Audio In/Out	Optional (RCA socket)
Speaker	Yes
Build-in MIC	No
Volnume adject	Yes

▶▶ Compression standard

Video Compression:	H.265/H.264/MJPEG
Video Bit Rate:	512Kbps~6144Kbps(main stream H.265) 64kbps~2048Kbps(sub stream H.265)
Dual Streams:	Yes
Triple Streams:	No

▶▶ General

Operating Conditions:	-10 °C ~ 60 °C, Humidity 95% or less (non-condensing)
Power Supply:	12 V DC ± 10%/PoE(Optional)
Power Consumption:	12 VDC ± 10%, Max Power Comsumption Less than 8W (When the infrared lamps turn on)
Weight:	0.56KG



+info

RESiSecurity

resisecurity.com

©2024- All rights reserved.

Product specifications and availability subject to change without notice.